

Set-up Instructions



Always wear ANSI approved safety goggles when assembling this product.



1 Lay out graphic and the display frame components.




2 Insert Banner Rods into the top and bottom pole pockets and press all parts of the display frame together firmly.



3 While the graphic is facedown, apply pressure to the Lower Clamp causing it to "snap" onto the Bottom Banner Rod.

5 Stand the entire display in an upright position.



4 Attach the Upper Clamp to the Top Banner Rod by flexing the Back Rod. Apply pressure to the Upper Clamp causing it to "snap" onto the Top Banner Rod.

- | | |
|-----------------------------------|-------------------------------------|
| <input type="checkbox"/> 8.5"x11" | <input type="checkbox"/> ___"x ___" |
| <input type="checkbox"/> 18"x24" | <input type="checkbox"/> ___"x ___" |
| <input type="checkbox"/> 24"x36" | <input type="checkbox"/> ___"x ___" |



Xtra Lite Warranty

Our X, S, T, E, P, M and B lines of frames come with a Lifetime Repair and Replace Warranty. If any of these frames break in the ordinary course of use, we will repair or replace the unit for \$10 per frame, plus return shipping. All other frames and accessories come with a One Year Manufacturer's Limited Warranty against defects.

© 1997-03, Xtra Lite Display Systems, Inc. Xtra Lite® is a registered trademark of Xtra Lite Display Systems, Inc. Innovation for Results™ is a trademark of Xtra Lite Display Systems, Inc. Protected by one or more of the following U.S. and International Patents: #5,839,705, #6,012,688, #6,454,227. Other patents pending. Printed in USA. All rights reserved.